

5

10

15

METHODS AND APPARATUSES
FOR MANAGING EFFLUENT
PRODUCTS IN A FUEL CELL SYSTEM

20

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates generally to fuel cell systems, and more particularly, the invention relates to methods and apparatuses for management of effluent products produced during an electrochemical reaction in a direct oxidation fuel cell system.

Background of the Invention

Fuel cells are devices in which an electrochemical reaction is used to generate electricity. A variety of materials may be suitable for use as a fuel depending upon the materials chosen for

the components of the cell and the intended application for which the fuel cell will provide electric power.

Fuel cell systems may be divided into "reformer based" systems (which make up the majority of currently available fuel cells), in which fuel is processed to improve fuel cell system performance before it is introduced into the fuel cell, and "direct oxidation" systems in which the fuel is fed directly into the fuel cell without internal processing.

Because of their ability to provide sustained electrical energy, fuel cells have increasingly been considered as a power source for smaller devices including consumer electronics such as portable computers and mobile phones. Accordingly, designs for both reformer based and direct oxidation fuel cells have been investigated for use in portable electronic devices. Reformer based systems are not generally considered a viable power source for small devices due to size and technical complexity of present fuel reformers.


Thus, significant research has focused on designing direct oxidation fuel cell systems for small applications, and in particular, direct systems using carbonaceous fuels including methanol, butanol, propanol, and formaldehyde. One example of a direct oxidation fuel cell system is a direct methanol fuel cell system. A direct methanol fuel cell power system is advantageous for providing power for smaller applications since methanol has a high energy density (providing compact energy storage), can be stored and handled with relative ease, and because the reactions necessary to generate electricity occur under ambient conditions.

DMFC power systems are also particularly advantageous since they are environmentally friendly. The chemical reaction in a DMFC power system yields only carbon dioxide and water as by products (in addition to the electricity produced). Moreover, a constant supply of methanol and oxygen (preferably from ambient air) can continuously generate electrical energy to maintain a continuous, specific power output. Thus, portable computers, mobile phones and other portable devices can be powered for extended periods of time while

substantially reducing and potentially eliminating at least some of the environmental hazards and costs associated with recycling and disposal of alkaline, Ni-MH and Li-Ion batteries.

The electrochemical reaction in a DMFC power system is a conversion of methanol and water to CO₂ and water. More specifically, in a DMFC, methanol in an aqueous solution is introduced to an anode chamber side of a protonically-conductive, electronically non-conductive membrane in the presence of a catalyst. When the fuel contacts the catalyst, hydrogen atoms from the fuel are separated from the other components of the fuel molecule. Upon closing of a circuit connecting a flow field plate of the anode chamber to a flow field plate of the cathode chamber through an external electrical load, the protons and electrons from the hydrogen atoms are separated, resulting in the protons passing through the membrane electrolyte and the electrons traveling through an external load. The protons and electrons then combine in the cathode chamber with oxygen producing water. Within the anode chamber, the carbon component of the fuel is converted by combination with water into CO₂, generating additional protons and electrons.

The specific electrochemical processes in a DMFC are:



The methanol in a DMFC is preferably used in an aqueous solution to reduce the effect of “methanol crossover”. Methanol crossover is a phenomenon whereby methanol molecules pass from the anode side of the membrane electrolyte, through the membrane electrolyte, to the cathode side without generating electricity. Heat is also generated when the “crossed over” methanol is oxidized in the cathode chamber. Methanol crossover occurs because present membrane electrolytes are permeable (to some degree) to methanol and water.

One of the problems with using DMFC power systems in portable power applications is the lack of a low-cost, effective method and system for removing effluents produced by the electrochemical reaction generally, and in particular, to remove water generated on the cathodic face of the membrane electrolyte or otherwise present in the cathode chamber. If
5 water generated in the cathode chamber collects on the cathode of the membrane or in the anode chamber, it may prevent oxygen from coming into contact with the cathodic electrocatalyst, interrupting productive oxidation of the fuel and generation of electricity.

In addition, the proper ratio of fuel to water delivered to the anode chamber in DMFC power
10 systems must be maintained. During operation, water molecules may be pulled across the membrane with hydrogen protons leading to excess water on the cathode side of the membrane and an increase in methanol concentration at the anode. The increased concentration of methanol may lead to additional methanol crossover resulting in decreased efficiency, a waste of methanol, and the generation of unwanted heat.

Theoretically, the effluents could be removed by venting the carbon dioxide out of the anode
15 chamber and evaporating the water from the cathode side of the membrane electrolyte with a low humidity ambient airflow. However, under many relevant conditions (e.g., low volume air flow, low ambient air pressure, moderate to high humidity), the water cannot be
20 effectively removed, and thus, alternate methods of eliminating water generated in the cathode are required.

According, the suitability of DMFC power systems for powering portable devices and consumer electronics is dependent upon the development of systems and methods for
25 eliminating and/or recirculating the effluent products produced during operation of the fuel cell. In addition, in order for DMFC power systems to be used effectively, they must be self-regulating and passively generate electrical power under benign operating conditions, such as ambient air temperature and pressure.

SUMMARY OF THE INVENTION

Accordingly, the present invention provides a water management system and method for managing effluent products generated as a result of fuel oxidation in a fuel cell system. More particularly, the present invention provides a water management system and method using an effluent gas (carbon dioxide) generated as a by-product of said fuel oxidation to remove or recirculate water from the fuel cell system.

The water management system and method according to the present invention is particularly well suited for use with a direct oxidation fuel cell system. Carbon dioxide produced from the oxidation of fuel is not directly exhausted from the fuel cell system but instead, used to remove/recirculate effluent water.

The present invention also provides a system and method for recirculating effluent water in a fuel cell system to maintain a preferred concentration of the carbonaceous fuel, thereby reducing the amount of water that must be stored with the carbonaceous fuel to maintain an optimum fuel concentration.

Accordingly, the below recited aspects of the present invention are directed to direct oxidation fuel cell systems, and more preferably to direct methanol fuel cell power systems.

In one aspect of the present invention, an effluent gas produced in an anode chamber of a fuel cell is collected and then exhausted through a cathode chamber of the fuel cell when the amount of effluent gas reaches predetermined value.

In another aspect of the present invention, a fuel cell includes an anode chamber having a fuel, a cathode chamber in fluid communication with an oxidizing agent, a proton conducting membrane electrolyte separating the chambers, and a first valve for controlling a first flow of a gas from the anode chamber into the cathode chamber. A related method for reducing the amount of water in the cathode chamber includes closing the first valve allowing an effluent

gas produced in the anode chamber to collect and opening the first valve when an amount of the effluent gas reaches a predetermined value.

In yet another aspect of the present invention, the fuel cell according to the second aspect further includes a gas plenum and a second valve. The first valve controls the first flow of the gas from the anode chamber into the gas plenum and the second valve controls a second flow of the gas collected in the gas plenum into the cathode chamber. A further related method includes opening the first valve allowing said first flow while said second valve is closed between said gas plenum and said cathode chamber. Effluent gas is then collected in the gas plenum via the first flow. When an amount of effluent gas collected in the gas plenum reaches a predetermined value, the first valve is closed and the second valve is opened, allowing the second flow.

In yet another aspect of the present invention, which may be used in conjunction with the above aspects, a fuel cell includes a fluid plenum, a third valve for controlling the second flow out of an outlet of the cathode chamber and into the fluid plenum and out an exhaust port and a fourth valve for controlling a third flow from the fluid plenum into the anode chamber.

The third valve of the fourth aspect allows the second flow between the outlet of the cathode chamber and the exhaust port when placed in a first position, and allows the second flow between the outlet and the fluid plenum when placed in a second position.

The fourth valve of the fourth aspect allows the third flow when placed in a first position and allows a fourth flow which controls a flow of fuel from a fuel supply cartridge to the anode chamber when placed in a second position.

In yet another aspect of the present invention, a fuel cell system includes an anode chamber having a fuel and a cathode chamber in fluid communication with an oxidizer. The cathode

chamber includes an inlet positioned in a first end of the cathode chamber and an outlet positioned adjacent a second end of the cathode chamber. The fuel cell according to the fifth aspect further includes a proton conducting membrane electrolyte separating the chambers and having an effluent gas-permeable portion allowing effluent gas produced in said anode chamber to flow into the cathode chamber, and a nozzle having an inlet positioned adjacent the gas-permeable portion in the cathode chamber and an outlet positioned adjacent outlet of the cathode chamber.

In yet another aspect of the present invention, a method for removing water in a cathode chamber of a fuel cell, the fuel cell including an anode, a cathode chamber having an inlet and an outlet, and a membrane electrolyte having a gas-permeable portion, the method includes directing an effluent gas produced in the anode chamber from the gas-permeable portion into the cathode outlet at a pressure, establishing a low pressure region adjacent the outlet, and inducing a flow from the inlet through the cathode chamber and exiting the outlet.

The above aspect may further include equalizing the pressure to an ambient pressure adjacent the outlet of the cathode chamber.

The flows recited in the above aspects may be communicated through the various elements via conduits and/or channels.

In addition, above aspects may include a controller for actuating the valves for controlling the flows.

BRIEF DESCRIPTIONS OF THE DRAWINGS

For a better understanding of the invention, reference is made to the drawings which are incorporated herein by reference and in which:

Fig. 1 is a schematic diagram of a water management system according to a first embodiment of the present invention.

5 Figs. 2A-2B are schematic diagrams of modes of gas flow into a direct oxidation fuel cell system according to the first embodiment for the present invention.

Fig. 3 is a schematic diagram of a water management system according to a second embodiment of the present the invention.

10 Fig. 4A-4B are schematic diagrams of gas flow and water return into a direct oxidation fuel cell system according to the second embodiment of the present invention.

Fig. 4C is a schematic diagram of a controller system for the water management system for the embodiments of the present invention.

15 Fig. 5 is a schematic diagram of a water management system according to a third embodiment of the present invention.

20 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The term "low humidity gas" as used herein refers to ambient air or other gas containing substantially less than its saturation level of water vapor, that is, having a relative humidity of less than 100%.

25 As shown in Figure 1, a direct oxidation fuel cell system 20 includes a membrane electrolyte assembly 21 having a proton-conducting, electronically non-conductive membrane electrolyte 26 disposed between an anode chamber 22 and a cathode chamber 24. The exact shape of the anode chamber and cathode chamber may be defined by a "flow field channel" which may be integrated into a flow field plate (not shown), which aids in distributing the

fuel and the oxidizing agent to the membrane electrolyte. In this diagram, each surface of the membrane electrolyte 26 is coated with electrocatalysts which serve as anode reactive sites 23 on the anode chamber side of the membrane and cathode reactive sites 25 on the cathode chamber side of the membrane. The anode and cathode reactive sites facilitate the electrochemical reactions of the DMFC.

It is worth noting that the electrocatalysts may be provided in other areas within the anode and cathode chambers, and thus, the invention is not limited to fuel cells where the catalysts are provided on the membrane electrolyte.

Diffusion layers 27 and 28, may be included and positioned on either side of the membrane. These layers provide a uniform effective supply of methanol solution (diffusion layer 27) to the anode reactive sites and a uniform effective supply of oxidizing agent (diffusion layer 28) to the cathode reactive sites. Diffusion layers 27 and 28 on each of the anode and cathode sides of the membrane electrolyte also assist in providing optimal humidification of the membrane electrolyte by assisting in the distribution and removal of water to and from the membrane electrolyte at rates that maintain a proper water balance in the DMFC power system. Moreover, each layer may be used with a flow field (not shown), to further aid in distributing fuel and oxidizer to the respective reactive sites.

The form of the anode chamber may be defined by a flow field plate (not shown) which guides the fuel mixture over the anode diffusion layer and also functions as a conductor (i.e., acts as the electrical anode), and an exhaust vent 30 which allows carbon dioxide created during oxidation of the fuel to pass out of the anode chamber. Similarly, the cathode chamber may include a flow field plate (not shown) which guides oxidizing agent in the chamber and also functions as a conductor (i.e., acts as the electrical cathode), an inlet 33 and an exhaust outlet 34 which allows air to flow through the cathode chamber so that an adequate supply of oxygen is insured for the reaction. One skilled in the art will appreciate

that air may flow from inlet 33 to outlet 34 and in the opposite direction, when the system is exposed to an ambient air pressure.

In a DMFC power system, an aqueous methanol solution, preferably a solution greater than 0% to about 100% methanol by volume, more preferably between greater than 0% to about 30% methanol by volume and most preferably approximately 3% methanol by volume, is used as the carbonaceous fuel reactant. The methanol solution circulates past the anode reactive sites 23. Upon the application of an electrical load between the flow field plates of the anode and the cathode chambers, the methanol solution disassociates, producing hydrogen protons and electrons, and generating carbon dioxide as a first by-product of fuel oxidation. Hydrogen protons migrate through the membrane electrolyte to the cathode chamber while electrons pass through the external load. The protons and electrons then combine with oxygen in the cathode chamber to form water, the second by-product of the reaction. The electrons are retrieved by the flow field plate of the anode chamber and carried through an external electrical load 29 to the flow field plate of the cathode chamber.

First Embodiment

In a first embodiment of the present invention, the flow of carbon dioxide is controlled through selective positioning of a vent valve 32 and an air inlet valve 36. The vent valve 32 is a two-way valve incorporated in an exhaust vent conduit 30 for controlling venting and accumulation of carbon dioxide (in conjunction with the air inlet valve) into a gas plenum 34. The air inlet valve 36 is a three-way valve incorporated at the intersection of an air inlet conduit 33a and a gas plenum conduit 34a, for controlling the flow of air and carbon dioxide (in conjunction with the vent valve 32) into the cathode chamber.

The positioning of the vent valve and the air inlet valve determine whether the water management system operates in an air inlet mode or a flush mode. The air inlet mode allows air from the air inlet conduit 33a to flow into the cathode chamber and out of the exhaust

outlet 34 carrying water away and refreshing the available oxygen for reaction at cathode reactive sites.

During the flush mode, a significant pressure drop caused by the buildup of carbon dioxide in the fluid plenum produces a high flow velocity of carbon dioxide from the gas plenum into the cathode chamber 24. This pressure drop also reduces the relative humidity of the carbon dioxide stored in the plenum, so that it can more readily absorb water in the cathode chamber. Thus, water is flushed from the cathode chamber by being blown out of the chamber by the pressure, and is evaporated due to the lowered relative humidity of the carbon dioxide.

Figure 2A illustrates the positions of vent valve 32 and the air inlet valve 36 during an air inlet mode. As shown, the vent valve 32 is open between the anode chamber 22 and the gas plenum 34 to allow carbon dioxide to accumulate in the gas plenum 34. The air inlet valve 36 is closed to the gas plenum 34 and open between an air inlet and the cathode chamber 24, so that the plenum can operate as a storage tank for the carbon dioxide and so that air may flow into the cathode chamber 24 as required for fuel oxidation.

Figure 2B illustrates the positions of the vent valve 32 and the air inlet valve 36 during a flush mode. In the flush mode, the vent valve 32 is closed between the anode chamber 22 and the gas plenum 34 and the air inlet valve 36 is open to the gas plenum 34 and closed between the air inlet and the cathode chamber. This positioning allows the stored carbon dioxide to flow out of the gas plenum and into the cathode chamber via conduit 40.

The vent valve 32 is preferably actuated to the flush mode position first, or concurrently with the air inlet valve 36. If the air inlet valve 36 is actuated before the vent valve, fuel may be expelled from the anode chamber into the cathode chamber adversely affecting the efficiency of the system as fuel is not used to generate power, but is wasted.

Because the membrane electrolyte operates more effectively within certain humidification parameters, the flush mode will not dehydrate or remove substantially all water from the membrane electrolyte.

- 5 In order for the flush mode to operate effectively, a predetermined sufficient amount of carbon dioxide is necessary to flush the water from the cathode reactive sites. Accordingly, the amount of carbon dioxide which has been generated must be determined.

10 In the present invention, the volume of carbon dioxide may be determined in the following ways:

- 15 (1) the level of fuel solution;
(2) the pressure level of the anode chamber;
(3) a time interval;
(4) power produced; and
(5) fuel concentration.

20 These methods and corresponding systems relate generally to active control of the flow of carbon dioxide to the cathode chamber. Such active control is generally managed by a controller (digital or analog) which actuates the valves for the various modes. However, it is worth noting that flow may also be controlled passively via relief valves, gas-permeable membranes, and other components that are well known to those skilled in the art.

Fuel Solution Level

- 25 As carbon dioxide is created and accumulates in the anode chamber and gas plenum, it pushes against the surface of the fuel solution. A predetermined displacement of carbonaceous fuel correlates to a predetermined volume of carbon dioxide sufficient to cause or assist in the removal of water from the cathode chamber. The system, however, is configured so that the predetermined displacement which determines when a flush mode is

required still allows normal power generation. Thus, electricity production will not diminish as the predetermined level is reached.

Accordingly, when the predetermined displacement level is reached, a sensor sends a signal
5 to a controller for actuating the valves to the flush mode positions.

The valves may be reset to air inlet mode by either the sensor, which indicates that the fuel is no longer displaced the predetermined amount, or by other means, including, but not limited to the use of a timer. The process is then repeated to continue generation of electricity.

10 Anode Chamber Pressure

A sufficient amount of carbon dioxide may be determined by detecting the level of pressure in at least one of the anode chamber 22 and the gas plenum 34. With this method and system, the pressure within the anode chamber is not fixed, rather it increases with the anodic
15 oxidation of the fuel solution due to the generation of carbon dioxide within the anode chamber 24.

In the air inlet mode, the pressure of the anode chamber 22 typically varies in relation to the water generated in the cathode chamber 24. The amount of carbon dioxide in the closed
20 volume of the anode chamber, is directly related to the amount of water generated in the cathode chamber. A predetermined level of pressure is associated with an amount of carbon dioxide sufficient to remove said water from the cathode chamber.

When a pressure sensor (e.g., diaphragm type, or resistive bridge) within a wall of the anode
25 chamber detects the predetermined pressure level, a controller actuates the valves to the flush mode positions. It is worth noting that this method and system may not require a controller. Specifically, the valves may be pressure-responsive release valves, actuated in response to a predetermined pressure level, or other fuel cell system operating characteristics.

Time Periods

Alternatively, the valves may be actuated between an air inlet mode and a flush mode positions after a predetermined period of time has elapsed during fuel cell operation. The controller tracks the amount of time when the cell is used for power. Since the power
5 provided would be at a predetermined voltage/current, the amount of carbon dioxide produced per unit time can be determined. Thus, after a predetermined operation time period has elapsed, the controller will actuate the valves to flush mode positions.

Power Production

10 In a similar method and system, the carbon dioxide level may be determined by tracking how much electric energy has been produced by the cell. Accordingly, a predetermined amount of energy (power produced over a time interval) correlates with a certain amount of carbon dioxide generated. The controller tracks the amount of energy output and actuates the valves when the predetermined amount of energy has been produced.

Fuel Concentration

The fuel in the anode chamber is a mixture of carbonaceous fuel (i.e., methanol) and water. Unless otherwise compensated, as the oxidation process occurs, the fuel becomes less concentrated in the solution, i.e., less fuel, more water. Because the concentration of the
20 carbonaceous fuel in the aqueous fuel solution and the amount of carbon dioxide generated are inversely related (provided that adjustments for introducing additional fuel are made), it is possible to determine how much carbon dioxide has been generated at the anode by measuring the concentration of the fuel in aqueous solution. Thus, a fuel concentration sensor (or sensors) sends fuel concentration signals to the controller. When the concentration
25 reaches a predetermined minimum indicating that fuel has been consumed to generate a sufficient amount of carbon dioxide to remove water from the cathode chamber, the controller actuates the valves to the flush mode positions.

Second Embodiment

Figs. 3 and 4A-4B illustrate a second embodiment according to the present invention. In this embodiment, a recirculation system provides active control for recirculating at least a portion of the water generated or transported across the membrane during fuel cell operation. By returning water to the anode chamber, fuel concentration is kept at an optimum level for efficient fuel cell operation, decreasing the volume of water that must be stored with the methanol in a fuel supply, thus allowing the DMFC power system to have an increased energy density. The recirculation system is preferably used in conjunction with the gas flow control methods and systems described in the previous embodiment.

The recirculation system includes a drain conduit 50 connected to the outlet of the cathode chamber, a drain valve 54, a drain outlet 51, a fluid plenum 57, a first fluid plenum conduit 52, a second plenum conduit 53, a return valve 56, a fuel supply conduit 59 and an anode supply conduit 60 connected to an inlet of the anode chamber.

The drain valve 54 is a three-way valve positioned at the intersection between the drain conduit 50, the drain outlet 51 and the first fluid plenum conduit 52, and is used either to exhaust water and gaseous effluent from the cathode chamber to the environment (connecting drain line 50 to the drain outlet 51), or to recirculate water removed from the cathode chamber to the cathode chamber (connecting drain line 50 to the first fluid plenum conduit 52).

The return valve 56 is also a three way valve positioned at the intersection of the second fluid plenum conduit 53, the anode inlet conduit 60 and the fuel supply conduit 59, and is used to keep a specific amount of fuel solution in the anode chamber (connecting the fuel supply conduit 59 to the anode supply conduit 60), and to recirculate the water recovered from the cathode chamber into the anode chamber (connecting second fluid plenum conduit 53 with the anode supply conduit 60). The valve 56 may also be used as a mixing chamber, for

mixing fuel solution with recirculated water from the cathode chamber for supply to the anode chamber.

Depending upon the state of the system generally, and the distribution of water in the DMFC power system, valves 54 and 56 may be actuated sequentially or simultaneously. Preferably, valves 54 and 56 are used in conjunction with the previous embodiment, the drain valve 54 and the return valve 56 include corresponding positions for the air inlet mode and the flush mode, and thus may be actuated upon detection of the same process variables and/or physical conditions for vent valve 32 and air inlet valve 36. Alternatively, the drain valve 54 and the return valve 56 may be activated independently of carbon dioxide flow control process.

Figures 4A and 4B illustrate the positions of the drain valve 54 and return valve 56 during an air inlet mode (Fig. 4A) and a flush mode (Fig. 4B). As shown in Fig. 4A, during an air inlet mode, the drain valve 54 exhausts water and carbon dioxide to the environment and the return valve 56 is closed to the fluid plenum 57 and open between the fuel supply cartridge 39 and the anode chamber 22. This establishes a throughput between the fuel supply 39 and the anode chamber 22 to discharge pressurized fuel into the anode chamber 22. Alternatively, during the air inlet mode, the return valve 56 (as shown in phantom) may periodically close to the fuel supply 39 and open to the fluid plenum 57 establishing a throughput between the fluid plenum 57 and the anode chamber 22 to return water to the anode chamber 22 for adjustment of the concentration of methanol solution. The return valve may also be closed to the fuel supply to halt the admission of new fuel during periods of low or no power generation.

Upon detection of the sufficient volume of carbon dioxide for the flush mode (Fig. 4B), the drain valve 54 is actuated to open to the fluid plenum 57 establishing a throughput between the cathode chamber 24 and the fluid plenum 57. Because pressure of the anode chamber 22 is higher than ambient pressure of the cathode chamber 24 during the air inlet mode, upon actuation to the flush mode of gas flow control, the pressure of the anode chamber 22 drops

substantially and equilibrates with the pressure of the cathode chamber 24. Water flushed from the cathode chamber 24 in the flush mode, therefore, is propelled by the flow of carbon dioxide, assisting in the collection of water in the fluid plenum 57.

5 Generally, since only a portion of water may be required for recirculation to the anode chamber, the drain valve 54 may remain open to the fluid plenum 57 for comparatively short intervals during the flush mode. Since the cathode and anode chambers, though connected together through valves 32 and 36, are together closed to the ambient by valves 36 and 54, some water pressure is maintained during recirculation of water from the cathode chamber 54
10 to the fluid plenum 57. Accordingly, if the drain valve 54 is closed to the plenum 57 (i.e., allowing fluid communication between drain conduit 50 and the drain outlet 51), the water within the fluid plenum can be discharged into the anode chamber upon opening of the return valve 56 between the second fluid plenum conduit and the anode supply conduit. It should be understood that additional valve(s) or plenum(s) (not shown) between return valve 56 and
15 anode chamber 22 may be used to control the flow of recirculated water and or fuel into anode chamber.

Figure 4C illustrates a generic controller for actuating the valves in both the first and second embodiments (independently and in conjunction). Accordingly, a controller 80, receiving
20 signals from sensor 90 (i.e., carbon dioxide levels) sends signals to valve actuators 82, 84, 86 and 88 at the appropriate times for the air inlet mode, the flush mode, fuel supply and water recirculation.

Third Embodiment

25 Fig. 5 illustrates a third embodiment according to the present invention. In this embodiment, a passive control system using a low humidity gas produced in the anode chamber removes water from the reactive sites in the cathode chamber using an enhanced air flow system.

The system according to this embodiment includes a membrane electrolyte assembly 62 disposed between an anode chamber 70 and a cathode chamber 72 of a fuel cell system 60. The assembly 62 includes a proton-conducting, electronically non-conductive membrane electrolyte 64 having a gas-permeable sector 66 selectively permeable to a desired effluent
5 gas, such as carbon dioxide, but not to water or fuel. A gas ejector 68 is connected to the cathode side of the gas-permeable sector 66.

The gas ejector 68 having a first end 67 and a second end 69, may be constructed preferably in a conical, parabolic or exponential shape. Each of these shapes causes the acceleration of
10 the flow velocity of carbon dioxide as it travels from the first end to the second end. To attain such a flow profile, the broadest portion of each shape is positioned on the first end, with the narrowest portion positioned at the second end.

The gas ejector 68 further includes a collar 65 disposed at the second end 69 of the gas
15 ejector 68, and is preferably positioned to encompass a low pressure region at the exit of the gas ejector, created by the flow of gas through the ejector. As air flows toward the low pressure region, the air flow is entrained in the low pressure region. The collar 65 then carries the entrained air, together with any water flushed from the cathode chamber and other effluents, toward an outlet 79.

Accordingly, the system operates in the following manner. Air, supplied to the cathode
20 chamber 72 from an external source, is delivered by an air inlet 74 to the cathode chamber. The low pressure region located at the second end 69 of the gas ejector draws air from the air inlet 74 toward the low pressure region. Air thereby is forced to flow into and through the
25 cathode chamber 72 at an enhanced velocity such that excess water accumulating in the cathode chamber, especially at the cathode reactive sites, is flushed or evaporated out of the chamber.

Having thus presented the present invention in view of the above described embodiments,
various alterations, modifications and improvements will readily occur to those skilled in the
art. Such alterations, modifications and improvements are intended to be within the scope
and spirit of the invention. Accordingly, the foregoing description is by way of example only
5 and is not intended as limiting. The invention's limit is defined only in the following claims
and the equivalents thereto.

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2